

Nissan Navara

POWER FARMING
520 Elizabeth Street Melbourne 3000 www.powerfarming.com.au

Specifications

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Engine											
2.5 litre intercooled turbo-diesel, DOHC	•	•	•	•	•	•	•	•	•	•	•
3.0 litre V6 intercooled turbo-diesel, DOHC										•	•
Displacement (cc)	2488	2488	2488	2488	2488	2488	2488	2488	2488	2993	2993
Bore x stroke (mm)	89x100	89x100	89x100	89x100	89x100	89x100	89x100	89x100	89x100	84x90	84x90
Max power (kW@rpm)	106@4000	126@4000	126@4000	126@4000	106@4000	126@4000	126@4000	120@4000	140@4000	170@3750	170@3750
Max torque (Nm@rpm)	356@2000	403@2000	403@2000	403@2000	356@2000	403@2000	403@2000	403@2000	450@2000	550@1750	550@1750

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Transmission											
6-speed manual	•	•	•	•	•	•	•	•	•		
5-speed automatic		Opt	Opt	Opt	Opt	Opt	Opt				
5-speed automatic with manual mode								Opt	Opt		
7-speed automatic with manual mode										•	•
Transfer case - Dual range 4x4 with electric 4WD selection	•	•	•	•		•	•		•	•	•
Ratio 1st manual	4.692	4.692	4.692	4.692	4.692	4.692	4.692	4.692	4.692		
Ratio 2nd manual	2.705	2.705	2.705	2.705	2.705	2.705	2.705	2.705	2.705		
Ratio 3rd manual	1.747	1.747	1.747	1.747	1.747	1.747	1.747	1.747	1.747		
Ratio 4th manual	1.291	1.291	1.291	1.291	1.291	1.291	1.291	1.291	1.291		
Ratio 5th manual	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000		
Ratio 6th manual	0.827	0.827	0.827	0.827	0.827	0.827	0.827	0.827	0.827		
Ratio reverse manual	4.260	4.260	4.260	4.260	4.260	4.260	4.260	4.260	4.260		
Final drive manual	3.538	3.692	3.692	3.692	3.538	3.692	3.692	3.538	3.692		
Ratio 1st automatic		3.827	3.827	3.827	3.827	3.827	3.827	3.827	3.827	4.886	4.886
Ratio 2nd automatic		2.368	2.368	2.368	2.368	2.368	2.368	2.368	2.368	3.169	3.169
Ratio 3rd automatic		1.519	1.519	1.519	1.519	1.519	1.519	1.520	1.520	2.027	2.027
Ratio 4th automatic		1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.411	1.411
Ratio 5th automatic		0.834	0.834	0.834	0.834	0.834	0.834	0.834	0.834	1.000	1.000
Ratio 6th automatic										0.864	0.864
Ratio 7th automatic										0.774	0.774
Ratio reverse automatic		2.613	2.613	2.613	2.613	2.613	2.613	2.613	2.613	4.041	4.041
Final drive automatic		3.538	3.538	3.538	3.538	3.538	3.357	3.357	3.538	3.133	3.133
Transfer ratio - low	2.625	2.625	2.625	2.625		2.625	2.625		2.625	2.625	2.625
Transfer ratio - high	1.000	1.000	1.000	1.000		1.000	1.000		1.000	1.000	1.000

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Dimensions											
Overall length (mm)	5140	5125	5125	5230	5125	5125	5125	5296	5296	5296	5296
Overall width (excluding mirrors) (mm)	1795	1850	1850	1850	1850	1850	1850	1848	1848	1848	1848
Overall height (w/o roof rail) (mm)	1740	1770	1770	1770	1780	1780	1780	1788	1795	1795	1795
Wheelbase (mm)	3200	3200	3200	3200	3200	3200	3200	3200	3200	3200	3200
Track front/rear (mm)	1550/1550	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570
Minimum turning circle kerb to kerb (m)	12.5	13.2	13.2	13.2	13.2	13.2	13.2	13.4	13.3	13.3	13.3
Tare mass incl options (kg)* manual/automatic	1638*	1754/1784*	1787/1817*	1957/1987	1885/1900	1990/2006	1850/1866*	1878/1893	1937/1977	2060	2104
Gross Vehicle Mass (GVM***) (kg)	2860	2860	2860	2860	2860	2860	2860	2805	2805	3010	3010
Carrying capacity (kg) manual/automatic	1222 ^a (manual)	1106/1076 ^a	1073/1043 ^a	903/873	975/960	870/854	1010/994 ^a	927/912	868/828	960 (automatic only)	906 (automatic only)
Ground clearance unladen (mm)	190	205	205	205	205	205	205	227	228	228	228
Overhang - front	800	800	800	800	800	800	800	866	866	866	866
Overhang - rear	1140	1125	1125	1230	1230	1125	1125	1230	1230	1230	1230
Angle of approach	32.0	32.0	32.0	32.0	32.0	32.0	32.0	30.0	30.0	30.0	30.0
Angle of departure	27.5	27.5	27.5	24.0	27.5	27.5	27.5	24.0	24.0	24.0	24.0
Tray length floor (mm)				1865	1513	1513		1511	1511	1511	1511
Tray length top (mm)				1830	1480	1480		1487	1487	1487	1487
Tray width floor (mm)				1560	1550	1550		1560	1560	1560	1560
Tray width top (mm)				1495	1494	1494		1496	1496	1496	1496
Tray width between wheel arches (mm)				1135	1134	1134		1130	1130	1130	1130
Tray width tailgate opening width				1435	1435	1435		1432	1432	1432	1432
Tray height (mm)				454	454	454		457	457	457	457

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Rated Towing Capacity*											
Trailer with brakes (kg)	3000	3000	3000	3000	2000	3000	3000	2000	3000	3000	3000
Trailer without brakes (kg)	750	750	750	750	750	750	750	750	750	750	750
Towball download (kg)	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table
Gross front axle (kg)	1365	1365	1365	1365	1365	1365	1365	1365	1365	1530	1530

Nissan Navara

POWER FARMING
520 Elizabeth Street Melbourne 3000 www.powerfarming.com.au

Specifications

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Illuminated ignition switch		•	•	•	•	•	•	•	•	•	•
Assist grip(s)	•	•	•	•	•	•	•	•	•	•	•
Door operated courtesy lights	•	•	•	•	•	•	•	•	•	•	•
Map lights					•	•	•	•	•	•	•
Driver's foot rest	•	•	•	•	•	•	•	•	•	•	•
Rear heater vents								•	•	•	•
Key ring											•

Instrumentation

Drive computer (distance to empty, average fuel economy, fuel economy record, elapsed time, drive distance, average speed and maintenance information)										•	•
Drive computer (distance to empty, average speed, average fuel consumption, journey time)								•	•		
Odometer, tachometer and dual trip meters	•	•	•	•	•	•	•	•	•	•	•
Digital clock	•	•	•	•	•	•	•	•	•	•	•
4WD indicator	•	•	•	•	•	•	•	•	•	•	•
Distance to next service	•	•	•	•	•	•	•	•	•	•	•
Low fuel warning light	•	•	•	•	•	•	•	•	•	•	•
Automatic transmission indicator in dash		Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	•	•
Automatic transmission shift interlock		Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	•	•
Headlights on - audible warning	•	•	•	•	•	•	•	•	•	•	•

Safety

Engine immobiliser	•	•	•	•	•	•	•	•	•	•	•
Driver and front passenger front-impact SRS airbags	•	•	•	•	•	•	•	•	•	•	•
Driver and front passenger side-impact SRS airbags								•	•	•	•
Front to rear SRS curtain airbags								•	•	•	•
Anti-lock braking system (ABS) and Electric Brake Distribution (EBD)	•	•	•	•	•	•	•	•	•	•	•
Vehicle Dynamic Control (VDC) with Active Brake Limited Slip Differential (ABLS)									•	•	•
Vehicle Dynamic Control (VDC)	•	•	•	•	•	•	•				
Turn-back safety power window (driver)								•	•	•	•
Collapsible steering column	•	•	•	•	•	•	•	•	•	•	•
Front seatbelts with load limiters and pretensioners	•	•	•	•	•	•	•	•	•	•	•
Front Emergency Locking Retractor (ELR) seatbelts	•	•	•	•	•	•	•	•	•	•	•
Rear Emergency Locking Retractor (ELR) seatbelts		•	•	•	•	•	•	•	•	•	•
Child restraint anchorages (3)								•	•	•	•
Child safety rear door locks					•	•	•	•	•	•	•
Door side intrusion bars	•	•	•	•	•	•	•	•	•	•	•
Multi-reflector headlights with headlight adjustment	•	•	•	•	•	•	•	•	•	•	•
Laminated windscreen	•	•	•	•	•	•	•	•	•	•	•
Day/night rear view mirror	•	•	•	•	•	•	•	•	•	•	•
Rear window demister with timer	•	•	•	•	•	•	•	•	•	•	•
Front variable intermittent & speed sensing windscreen wipers	•	•	•	•	•	•	•	•	•	•	•
Driver's seatbelt warning lamp	•	•	•	•	•	•	•	•	•	•	•
Door ajar warning light	•	•	•	•	•	•	•	•	•	•	•
Reversing Camera with Predictive Path Technology											•
Front Protection Accessory								Opt-	Opt-	Opt-	Opt-

Exterior

Alloy sports bar				•				•	•	•	•
Black Satin Sports bar with integrated high mounted stop light											•
Privacy Glass (2nd Row)										•	•
Front fog lights										•	•
5 channel Utili-Track system™								•	•	•	•
Tie down points				•	•	•					
Protective tub liner				•							•
Smoked bonnet protector											•
Side steps			•	•				•	•	•	•
Antenna	•	•	•	•	•	•	•	•	•	•	•
Remote keyless entry (integrated into key)	•	•	•	•	•	•	•	•	•	•	•
Front bumper body colour	•	•	•	•	•	•	•	•	•	•	•
Chrome step type rear bumper			•	•				•	•	•	•
Chrome frame grille	•	•	•	•	•	•	•	•	•	•	•
Lockable fuel lid	•	•	•				•	•	•	•	•
Remote fuel lid				•	•	•					
Front and rear mudflaps	Front	Front	Front	•	•	•	Front	•	•	•	•

Nissan Navara

POWER FARMING
520 Elizabeth Street Melbourne 3000 www.powerfarming.com.au

Specifications

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Front towing hook	•	•	•	•	•	•	•	•	•	•	•
Power door mirrors			•	•				•	•	•	•
Power folding door mirrors with integrated indicator lights										•	•
Door mirrors	Black	Black	Body Coloured	Body Coloured	Black	Black	Black	Body Coloured	Body Coloured	Chrome	Chrome
Door handles	Black	Black	Body Coloured	Body Coloured	Black	Black	Black	Black	Black	Black	Black
Rear window guard frame					•	•					

Colours

Arctic White (326)								•	•	•	•
Silver Lightning (KLD)*								•	•	•	•
Tuscan (A32)*								•	•	•	•
Altitude Blue (RAK)*								•	•	•	•
Flame Red (Z10)								•	•	•	•
Midnight Black (GND)*								•	•	•	•
Blue Velvet (BW9)								•	•	•	•
Brilliant Silver (K23)*	•	•	•	•	•	•	•				
Cosmic Black (G42)*		•	•	•	•	•	•				
Slate Grey (K21)*	•	•	•	•	•	•	•				
Polar White (QM1)	•	•	•	•	•	•	•				
Titanium (KAC)*		•	•	•	•	•	•				

Warranty

3 year / 100,000kms	•	•	•	•	•	•	•	•	•	•	•
3 year 24-Hour Roadside Assistance Program	•	•	•	•	•	•	•	•	•	•	•
Genuine Nissan Extended Warranty	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt

** GVM = Gross Vehicle Mass. GVM includes the driver, passengers, full fuel tank and luggage.

Tare mass = unladen mass of vehicle and 10 litres of fuel, excludes tray body for Cab Chassis vehicles.

Δ Including optional tray.

* Indicates a metallic paint, which is available at extra cost.

° Figures have been calculated in accordance with ADR81/02 (combined fuel consumption data). Actual fuel consumption will vary depending on driving conditions, driver behavior, the condition of your vehicle and the accessories fitted.

† Towing capacity is subject to towbar/towball capacity. The capacity may be reduced if a non genuine Nissan towbar is fitted. The permitted download is directly related to the laden mass of vehicle. The maximum towball download is 300kg (4WD models).

~ The fitment of front protection systems and accessories having a combined weight in excess of 55 kgs will require a Positive Bonnet Restraint System & Nissan H/D front suspension springs.

Single and King Cab models

Towball download	Vehicle Mass
80kg	GVM** (All variants)
100kg	Reduced loaded vehicle mass below GVM** by 30kg
150kg	Reduced loaded vehicle mass below GVM** by 110kg
200kg	Reduced loaded vehicle mass below GVM** by 185kg
250kg	Reduced loaded vehicle mass below GVM** by 250kg
300kg	Reduced loaded vehicle mass below GVM** by 310kg

4WD Dual Cab models

Towball download	Vehicle Mass
150kg	GVM** (All variants)
200kg	Reduced loaded vehicle mass below GVM** by 60kg
250kg	Reduced loaded vehicle mass below GVM** by 130kg
300kg	Reduced loaded vehicle mass below GVM** by 200kg

2WD Dual Cab models

Towball download	Vehicle Mass
70kg	GVM** (All variants)
100kg	Reduced loaded vehicle mass to below GVM** by 40kg
150kg	Reduced loaded vehicle mass to below GVM** by 110kg
200kg	Reduced loaded vehicle mass to below GVM** by 180kg

Opt Optional Not available Standard

If the loaded vehicle's rear mass is reduced as shown in the tables, the towball download can be increased correspondingly. Accordingly, if the laden mass is 180kg less than the GVM** a towball download of 200kg is approved (2WD). Different trailer types and different trailer manufacturers have varying towball downloads. The customer will need to contact the trailer manufacturer for information as to the download. Nissan is not able to make any recommendation on the use or suitability of load-levelling or weight distribution devices to be fitted to the vehicle. Customers should contact the manufacturers of these devices for further information.

POWER FARMING

520 Elizabeth Street Melbourne 3000 www.powerfarming.com.au