		KVF750 4X4 EPS	<b>₩∀</b> F650 4 <b>X</b> 4	₩¥¥360 4 <b>X</b> 4	<b>*KVF3</b> 00	
Engine Type		4-stroke, SOHC, liquid cooled, v-twin		4-stroke,SOHC, air cooled, single cylinder	4-stroke,SOHC, liquid cooled, single cylinder	
Displacement		749 cm <sup>3</sup>	633 cm <sup>3</sup>	362 cm <sup>3</sup>	271 cm <sup>3</sup>	
Fuel System		Electronic Fuel Injection: ø36 mm x 2 (Mikuni)	Keihin CVKR - D32 x 2	Keihin CVK 34	Keihin CVK 32	
Starting		Electric	Electric	Electric with r	etric with recoil back-up	
Transmission		Continuously variable belt-drive transmission with high and low range, plus reverse, and Kawasaki Engine Brake Control			Continuously variable transmission, centrifugal clutch with Forward and Reverse.	
Final Drive		Selectable four-wheel drive with Variable Front Differential Control, shaft			Shaft 2WD	
Suspension	Front	Independent double wishbone, 5-way adjustable preload shock absorbers.	Independent Macpherson strut		Independent double wishbone, 5-way adjustable preload shock absorbers.	
	Rear	Independent double wishbone, 5-way adjustable preload shock absorbers.	Independent double wishbone, 5-way adjustable preload shock absorbers.	Aluminium swingarm with gas charged rear shock absorber, 5 way preload adjustment	Swingarm with 5-way adjustable preload	
Ground Clearance		Centre of Chassis - 247 mm	Rear Final Gear Case - 185 mm. Centre of Chassis - 230 mm	Rear Final Gear Case - 185 mm. Centre of Chassis - 235 mm.	155 mm	
Wheel travel	Front	171 mm	170 mm	170 mm	131 mm	
	Rear	200 mm	184 mm	180 mm	141 mm	
Brakes	Front	Dual hydraulic discs with twin piston callipers		Dual hydraulic disc with single piston callipers	Dual hydraulic disc with single piston callipers	
	Rear	Sealed, oil-bathed, multi-disc			Disc with single piston calliper and mechanical parking brake	
Wheels	Front	12.0 × 6.0	12.0 × 6.0	12.0 × 6.0	9.0 x 6.0	
	Rear	$12.0 \times 7.5$	12.0 × 7.5	$12.0 \times 7.5$	10.0 x 8.5	
Tyre Size	Front	$25 \times 8$ -12 Tubeless	$25 \times 8-12$ Tubeless	$25 \times 8$ -12 Tubeless	22 x 7-10 Tubeless	
	Rear	$25 \times 10$ -12 Tubeless	$25 \times 10$ -12 Tubeless	$25 \times 10$ -12 Tubeless	22 x 10-10 Tubeless	
LxWxHmm		2,195×1,166 × 1,233	2,185×1,212×1,164	2,065×1,205×1,145	1,915 x 1,080 x 1,170 mm	
Wheelbase		1,284 mm	1,294 mm	1,250 mm	1,165 mm	
Seat height		903 mm	862 mm	895 mm	845 mm	
Fuel capacity		19 litres	18 litres	13.5 litres	12 litres	
Curb Mass#		296 kg	293 kg	290 kg	243 kg	
Vehicle Max Load		215 kg incl rider & cargo	215 kg incl rider & cargo	205 kg incl rider & cargo	165 kg including rider & cargo	
Max Load Front Rack		40 kg	40 kg	40 kg	20 kg	
Max Load Rear Rack		80 kg	80 kg	70 kg	30 kg	
Max Towing Capacity *including trailer & cargo		Tow hitch: 40 kg Towable weight: 567 kg*	Tow hitch: 40 kg Towable weight: 567 kg*	Tow hitch: 40 kg Towable weight: 500 kg*	Tow hitch: 14 kg Towable weight: 227 kg*	
Colours "Curb mass includes full fuel tank and al		Scout Green	Woodsman Green	Aztec Red	Aztec Red	

<sup>\*</sup>Curb mass includes full fuel tank and all fluids at correct levels.