

Engine specifications.

Engine	TSI300	TDI340	TDI400	
Type	Inline 4 Cylinder, DOHC, 16 Valve	Inline 4 Cylinder, DOHC, 16 Valve	Inline 4 Cylinder, DOHC, 16 Valve	
Capacity, litres/cc	2.0 / 1,984	2.0 / 1,968	2.0 / 1,968	
Bore x Stroke / Compression ratio	82.5mm x 92.8mm/ 9.6:1	81.0mm x 95.5mm / 16.5:1	81.0mm x 95.5mm / 16.5:1	
Maximum power, kW @ rpm	118 @ 3,750	90 @ 3,750	120 @ 4,000	
Maximum Torque, Nm @ rpm	300 @ 1,750-2,250	340 @ 1,750-2,250	400 @ 1,500-2,500	
Induction Type	Single turbocharger	Single turbocharger	Bi-turbochargers	
Fuel System	Petrol Direct System	Common Rail Direct Injection	Common Rail Direct Injection	
Intercooled	Yes	Yes	Yes	
Emissions standard	Euro 4	Euro 5* with Diesel Particle Filter (DPF)	Euro 5* with Diesel Particle Filter (DPF)	
Fuel Type	Petrol	Diesel	Diesel	
Fuel Tank Capacity	80 Litres	80 Litres	80 Litres	
Battery	450 Amp 95Ah	450 Amp 95Ah	450 Amp 95Ah	
Transmission				
Transmission	6 Speed Manual	6 Speed Manual	6 Speed Manual	
Driven wheels	Rear wheel drive	Rear wheel drive	Selectable 4MOTION / Permanent 4MOTION (Ultimate)	
Final Drive	4.3	4.3	4.1	
Low range reduction for vehicles with selectable 4MOTION: 2.72	1st Gear: 4.82	1st Gear: 4.82	1st Gear: 4.82	
	2nd Gear: 2.54	2nd Gear: 2.54	2nd Gear: 2.54	
	3rd Gear: 1.49	3rd Gear: 1.49	3rd Gear: 1.49	
	4th Gear: 1.0	4th Gear: 1.0	4th Gear: 1.0	
	5th Gear: 0.76	5th Gear: 0.76	5th Gear: 0.76	
	6th Gear: 0.64	6th Gear: 0.64	6th Gear: 0.64	
	Reverse Gear: 4.37	Reverse Gear: 4.37	Reverse Gear: 4.37	
Wheels and Tyres	Amarok	Amarok Trendline	Amarok Highline	Amarok Ultimate
Wheels	Steel 6.5J x 16	Alloy "Taruma" 6.5J x 16	Alloy "Durban" 7.5J x 18	Alloy "Alastaro" 8.0J x 19
Tyres	205 R16 C 110/108T	245 / 70 R16 111T	255 / 60 R18 112T	255 / 55 R19 111T
Fuel Consumption – ADR81/02	Comb / Urban / Ex Urban • CO₂			
2WD TSI300, Litre/100km • CO ₂	9.6 / 12.7 / 7.9 • 228g/km			
2WD TDI340, Litre/100km • CO ₂	7.4 / 9.2 / 6.5 • 194g/km			
2WD TDI400, Litre/100km • CO ₂	7.7 / 9.5 / 6.8 • 203g/km			
4MOTION TDI400, Litre/100km Selectable • CO ₂	7.9 / 9.7 / 7.0 • 209g/km			
4MOTION TDI400, Litre/100km Permanent • CO ₂	7.9 / 9.7 / 7.0 • 209g/km			

Volkswagen Amarok Series

POWER FARMING
520 Elizabeth Street Melbourne 3000 www.powerfarming.com.au

Dimensions.

Dimensions	Amarok	Amarok Trendline, Highline and Ultimate
Length, mm	5,181	5,254
Width, mm	1,944 (2,228 including mirrors)	1,944 (2,228 including mirrors)
Height, mm	1,834	1,834
Wheelbase, mm	3,095	3,095
Ground clearance, mm	230 (192 with 4MOTION underbody protection)	192 with 4MOTION underbody protection
Entry angle	28°	28°
Departure angle	28°	23.6°
Ramp angle	23° (21.4° with 4MOTION)	21.4° with 4MOTION
Wadding depth	500mm	500mm
Cargo Area		
Rear tailgate width, mm	1,411	
Rear tailgate height, mm	508	
Load area, m ²	2.52	
Length, mm	1,555	
Width at widest point, mm	1,620	
Width at wheel arch, mm	1,222	
Height from ground, mm	780	
Warranty		
Vehicle	3 Years, Unlimited km	
Paint / Corrosion	3 Years / 6 Years	
Road side assistance	3 Years, Unlimited km	

Weights.

Weights	Amarok	Amarok Trendline	Amarok Highline	Amarok Ultimate			
GVM 3,040kg	Standard (Heavy Duty) ¹	Standard (Heavy Duty) ¹	Standard (Heavy Duty) ¹	Standard (Heavy Duty) ¹			
GVM 2,820kg	Optional (Comfort Suspension)	Optional (Comfort Suspension)	Optional (Comfort Suspension)	Optional (Comfort Suspension)			
Roof load, kg	100	100	100	100			
Towing capacity, braked / unbraked	2,800kg / 750kg	2,800kg / 750kg	2,800kg / 750kg	2,800kg / 750kg			
Towing downball load	280kg	280kg	280kg	280kg			
	Amarok TSI300 2WD	Amarok TDI340 2WD	Amarok TDI400 2WD	Amarok TDI400 4MOTION	Amarok Trendline TDI400	Amarok Highline TDI400	Amarok Ultimate TDI400
Unladen Mass ² kg	1,842	1,861	1,881	1,978	2,020	2,047	2,098
Payload at 3,040kg GVM ³	1,197	1,178	1,158	1,061	1,019	992	941

Suspension and brakes specifications.

Suspension & Steering	
Front axle	Transverse link with A-frame arm double wishbone and anti-roll bar
Rear axle	Multi-layer rigid axle with leaf spring and stabiliser bar
Steering	Rack and pinion power steering
Turning Circle	12.95m
Brakes	
Front brakes	303mm Disc brakes
Rear brakes	292mm Drum brake
Brake systems	ESP, off-road ABS, ASR, EDL and Hill Holder